




SecuTAC 555

Multi-media Fingerprint Time Attendance and Access Control



Introduction

SecuTac 555 time attendance and access control terminal can manage 10,000 templates in 1.5 second (1: N Identification). SecuTac 555 uses high image quality optical fingerprint sensor. The patented optical sensor is resistant to scratches, impact, vibration and electrostatic shock.

Because of the common development platform, existing customer will be able to use SecuTac 555 and coexist with any existing SecuTac reader without enrolling the users. The Secutac 555 can be used in multifactor authentication that supports finger print, password, proximity and smart card. It also has an option for WiFi and GPRS connectivity

SecuTac 555 has camera and 3.5" color TFT LCD Display so it can display the individual graphical interfaces and personal color photos. It comes standard with TCP/IP,RS 232/485,USB Host,USB Client,8 function keys,T9 Input method, back up battery and has access control connectivity for weigand in/out, Door lock connection, Alarm Bell, remote to Exit Switch

secuTAC

Features:

* Multimedia

3.5" TFT screen support different Multimedia formats. Internal Camera and Photo-ID support the user's photo display and make T&A application more visible and reliable.

* Time & Attendance

Built-in backup battery protects data.
Storage Capacity: Store up to 8,000 templates (1: N) and 200,000 records.
More practical functions such as SMS, T9 input, Work-code enable user-friendly.
Offer a wide selection in authentication mode and easy security system upgrade with combination of fingerprint, password and ID/MIFARE/HID card.

* Access Control

Monitor employee's movement at any time. Provide extra security with 50 time zone, user grouping, and professional unlocking combination function, easy integration with door lock system.

* Communications

Versatile interface options including RS232/485, TCP/IP, USB Host, USB Client, Optional WIFI and GPRS;

Configuration:



Specifications:

Fingerprint Capacity	8000 templates
Transaction Capacity	200,000
Hardware Platform	ZEM600
Sensor	Optical Sensor
Algorithm Version	Finger v10.0
Communication	RS232/485, TCP/IP, USB-client, USB-host
Standard Functions	Workcode, SMS, DLST, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 input, photo-ID, Web server, Camera, built-in battery
Access Control Interface for	Lock, door sensor, exit button, alarm, Door Bell, Anti-pass back
Wiegand Signal	Input & Output
Optional Functions	ID/Mifare/HID, printer, soap, WIFI, GPRS, RIS
Display	3.5 inches TFT Screen
Power Supply	12V DC 3A
Operating Temperature	0°C - 45°C
Operating Humidity	20%-80%
Dimension	225x165.5x50 mm
Weight With Package	2.05 kg



For more information contact:

Cardz Middle East

PO Box: 95781, Dubai, United Arab Emirates

Tel: +97142293780, Fax: +97142293790

Email: sales@cardzme.com, Web: www.cardzme.com